

The Runco XP-65DHD plasma establishes a higher threshold for flat panel display products. Runco's XP-65DHD's outstanding performance is so good that it was the first plasma to meet stringent THX certification standards.



|                              |   |
|------------------------------|---|
| Native Resolution:           | 1920 x 1080   |
| Screen Size:                 | 65 in. (diagonal)   |
| Screen Aspect Ratio:         | 16:9  |
| Image Area (W x H inches)    | 57" x 32"   |
| DTV Compatibility:           | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p (24,50,60 Hz)  |
| Contrast Ratio:              | 400:1 (measured at 100 lux); 5000:1 maximum   |
| ISF Settings:                | Yes   |
| Data/Graphics Compatibility: | Up to 1920 x 1200   |
| Power Requirements:          | 100-240V AC, 50/60Hz  |
| Power Consumption:           | 790 W (.1 watts in standby), maximum  |
| Operating Environment:       | 40° - 95° F (5° - 35°C), 20-80% Humidity (non-condensing)<br>Altitude = up to 9,100 feet (2,800m)   |
| Dimensions (w/o stand)       | Width: 62.33 in (1582.4 mm)<br>Depth: 4.16 in. (104.1 mm)<br>Height: 39.7 in (958 mm)   |
| Weight:                      | 163lbs. (73.98 kg)  |
| Regulatory Approvals:        | FCC Class B, CE, C-Tick   |
| Limited Warranty:            | Two years parts and labor from the date of shipment from Runco. RuncoCare™ and Runco RedCarpet™ plans are also available.                     |
| The XP-65DHD ships with:     | Power cords (US, EU), remote control and two batteries (AAA), warranty information and registration card, Runco Operating manual, cable ties. |

### Runco DHD Controller Specifications

|                                 |  |
|---------------------------------|--|
| Aspect Ratios:                  | 4:3, 16:9, Letterbox, VirtualWide™, Native, VirtualCinema™ and Cinema  |
| Video Processing:               | ViVix III™ 1080p output  |
| Video Standards:                | NTSC, PAL, ATSC and SECAM  |
| Supported Signal Timings:       | 1080p (23.98, 24, 50, 59.94, 60), 1080i (50, 50 Australia, 59.94, 60), 720p (23.98, 24, 25, 29.97, 30, 50, 60), 576p/i, 480p/i, SCART RGB, standard PC timings   |
| Output:                         | (1) HDMI v1.3 w/ HDCP and Deep Color up to 12 bits/channel; (1) RJ-11 for display control; (1) RJ-11 for display control   |
| Inputs:                         | (1) Composite; (2) S-Video; (1) Component; (2) HD - R (Pr), G (Y), B (Pb), H, V; (2) HDMI v1.3 w/HDCP and Deep Color up to 12 bits/channel   |
| Communications Control Ports:   | Discrete infrared remote, (1) RS-232 9 pin connector; front panel  |
| Screen Trigger/ Masking Output: | (3) +12 VDC, each rated at 250 mA with over-current protection   |
| Power Requirements:             | 100-240V AC (auto sensing) 50/60 Hz, 40W   |
| Dimensions:                     | Width: 17 1/2 in. (444.50 mm); Depth: 11 3/16 in. (284.10 mm); Height: 3 3/4 in. (95.25 mm), Weight: 13 lbs. (5.9 kg)  |
| Features:                       | Highly-compatible with today's video sources, fully-compliant HDMI/HDCP repeater, full ISF™ calibration controls, easy firmware upgrades via USB or serial, customizable splash screen and side-curtain colors |
| BRiC Tool:                      | Backup, Recovery and Clone tool for ease of saving, restoring or cloning calibrations settings   |